



QUALITY PACKAGED CONCRETE PRODUCTS NATIONWIDE

Description:

PAKMIX® Fast Set Accelerator is a premium cementitious, non-chloride accelerator designed to assist PAKMIX® Concrete Mix and other PAKMIX® cement based products achieve faster setting times. This product is acceptable for use with rebar, wire mesh or metal. When mixed with PAKMIX® cement products containing aggregates (*concrete*), rapid strength gains can be expected in addition to early setting times.

Suggested Uses:

- ▶ Fence Post
- ▶ Mailboxes
- ▶ Lamp Post
- ▶ Swing Sets
- ▶ Game Poles

Directions for use & Yields:

Thoroughly mix entire contents of the container with a bag of concrete to achieve accelerated set-times. Under normal conditions PAKMIX® Fast Set Accelerator will achieve the following initial set times.

60 lb. Bag	30-40 minutes*
80 lb. Bag	45-55 minutes*
90 lb. Bag	50-60 minutes*

**Set times may vary due to temperature and cement content in the concrete mix.*

May also be use to accelerate the set times of other PAKMIX® cement products (*i.e. PAKMIX® Sand Mix, PAKMIX® Mortar Mix, etc.*).

Items you may need:

- ▶ Wheelbarrow or Mixing Tub
- ▶ Shovel
- ▶ Mixing Hoe
- ▶ Hose

Packaging:

Packaged in 1-1/2 lb. containers.

For Best Results:

When using in temperatures below 45° F it is recommended to use warm water. Mix entire contents of the container to achieve minimum set times. It is recommended to use this product only when freezing is not imminent.

Clean Up:

Clean up is easy with soap and water. Rinse tools before material hardens.




Caution:

This product contains cement. As with any cementitious material, direct contact may irritate eyes and skin. Wear protective clothing, gloves and eye protection when using the product. If any material gets into the eyes, rinse immediately and contact a physician. Wash exposed skin areas promptly with water. Do not take internally.

Harmful if inhaled. This product contains Free Silica (CAS# 14808-60-7). When Free Silica is inhaled, it may cause delayed respiratory and other health problems. Free Silica has been listed by I.A.R.C. as a possible carcinogen based upon laboratory animal test data and limited evidence of human carcinogenicity. Avoid breathing cement dust. Keep the pail closed when not in use, and use only in well-ventilated areas. Follow OSHA Safety and Health Standards for crystalline silica. If the product must be used in an enclosed area, use a NIOSH approved dust respirator.

Keep Out of Reach of Children:

Material safety data sheet available upon request.



FAST SET ACCELERATOR

FAST SET ACCELERATOR
PRO LINE



605 Industrial Way, Dixon, California 95620
(800) 272-5649 • FAX (707) 693-9349
www.pakmix.com