



BLACKTOP PATCH

QUALITY PACKAGED CONCRETE PRODUCTS NATIONWIDE

Description:

PAKMIX® BlackTop Patch is a ready-to-use mixture of asphalt and graded aggregates ideal for the repair of blacktop surfaces. Pre-blended – no mixing is required before use.

Suggested Uses:

- For fast and easy patching of:
 - ▶ Blacktop Driveways & Walkways.
 - ▶ Parking Areas.

Preparation:

All surfaces should be clean and free of oil, gas, paint, grease, etc., before applying material. Remove all loose particles and foreign matter from area to be repaired.

Important: Square edges of hole or crack.



Directions:

Place PAKMIX® BlackTop Patch in area to be repaired. Spread BlackTop Patch to a level of about one inch higher than the surrounding area, then compact with a hand tamper, lawn roller or by driving over the patch with a car wheel.

Items you may need:

- ▶ Hand Tamper.
- ▶ Shovel or Hoe.
- ▶ Lawn Roller.

Packaging & Yields:

One 50 pound (50 lb.) bag covers approximately 4 sq. ft. x one inch thick or approximately 1/3 (.33) cu. ft. compacted volume.

For Best Results:

Compaction of the patch is very important. The more compaction the better the patch. Under normal conditions, the



newly paved area may be used immediately. To speed hardening and eliminate a tacky surface, dust with dry sand or Portland cement. The PAKMIX Blacktop Patch hardens and cures through a process of evaporation. Cooler climates will require a longer curing time.

Important: Following prolonged storage, PAKMIX® BlackTop Patch may feel hard in the bag. This is normal and will not adversely affect the mix. Kneading the material before opening the bag will loosen the material to a workable consistency. In cool and cold weather, keep the bags of material in a warm area for at least 24 hours before using.

Clean Up:


Clean up with mineral spirits.

Caution:

PAKMIX® BlackTop Patch contains petroleum asphalt. As with any petroleum-based material, direct contact may irritate eyes and skin. Wear protective clothing, gloves and eye protection when using the product. If any material gets into the eyes, rinse immediately and contact a physician. Wash exposed skin areas promptly with water. Do not take internally.

Keep Out of Reach of Children:

Material safety data sheet available upon request.



605 Industrial Way, Dixon, California 95620
(800) 272-5649 • FAX (707) 693-9349
www.pakmix.com

BLACKTOP PATCH
PRO LINE