

Asphalt Crack Filler

Description

Pakmix[®] Asphalt Crack Filler is a flexible, ready-to-use, black colored crack filler to repair cracks up to 3/8" wide in asphalt surfaces. Repairs are fast, easy, and self-leveling. The crack filler forms a tough, elastic sealer strip.

Suggested Uses

For fast and easy patching of cracks in the following:

- Blacktop driveways and walkways
- Parking areas
- Expansion joints

Preparation

All surfaces should be clean and free of oil, gas, paint, grease, etc. before applying material. Remove all loose particles of dirt and debris from the crack.

Directions for Mixing

Mix the contents of the container by shaking well. Snip or cut the applicator top to desired size. Simply squeeze the bottle pushing the material into the crack. Fill the crack until the crack filler levels with the existing surface.

Items You May Need

- Scissors or knife
- Brush for cleaning

Packaging and Yields

1 gal. will fill a crack approximately 1/4" wide x 1/4" deep x 150 linear feet long. Material comes packaged in 11 oz. tubes, 1 qt. and 1 gal. plastic bottles.

For Best Results

Make sure the crack is clear of all dirt and debris. Do not use in temperatures below 50° F or if rain is expected. Drying time is 24-48 hours depending on weather conditions and thickness of the material. To speed hardening and eliminate a tacky surface, dust with dry sand or Portland cement. Cooler climates will require a longer curing time.

Clean Up

Clean immediately with soap and water. Hardened material may be removed using mineral spirits.

Keep from Freezing

Materials Safety Data Sheet available upon request.

1 qt. Bottle



1 gal. Jug



11 oz. Tube



CAUTION • AVOID CONTACT WITH SKIN • INJURIOUS TO EYES Pakmix[®] Asphalt Crack filler contains petroleum asphalt. As with any petroleum based material, direct contact may irritate eyes and skin. Wear protective clothing, gloves, and eye protection when using the product. If any material gets into the eyes, rinse immediately and contact a physician. Wash exposed skin areas promptly with water. Do not take internally.

EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.

KEEP OUT OF REACH OF CHILDREN

DISCLAIMER AND LIMITATION OF LIABILITY This material is warranted to be of good quality. Upon receipt of a claim within one year from the date of sale, defective material will be replaced or the purchase price refunded at the option of the manufacturer. Except for the foregoing, all warranties, expressed or implied, including merchantability and fitness for a particular purpose, are excluded. No liability is assumed for any consequential, incidental or special damages arising directly or indirectly from the use of the material.