

# **Blacktop Patch**

## **Description**

Pakmix<sup>®</sup> Blacktop Patch is a ready-to-use mixture of asphalt and graded aggregates ideal for the repair of blacktop surfaces. Pre-blended; no mixing is required before use.

## **Suggested Uses**

For fast and easy patching of:

- Blacktop driveways and walkways
- Parking areas

## **Preparation**

All surfaces should be clean and free of oil, gas, paint, grease, etc. before applying the material. Remove all loose particles and foreign matter from the area to be repaired.

Important: Square edges of hole or crack.



### **Directions**

Place Pakmix<sup>®</sup> Blacktop Patch in the area to be repaired. Spread the Blacktop Patch to a level of about 1" higher than the surrounding area and then compact with a hand tamper, lawn roller, or by driving over the patch with a car wheel.

## **Items You May Need**

- Hand tamper
- · Shovel or hoe
- Lawn roller

## **Packaging and Yields**

1 – 50 lb bag covers approximately 4 sq. ft. x 1" thick or approximately 1/3 (.33) cu. ft. compacted volume.

### **For Best Results**

Compaction of the patch is very important; the more compaction the better the patch. Under normal conditions the newly paved area may be used immediately. To speed hardening and eliminate a tacky surface, dust with dry sand or Portland cement. The Pakmix<sup>®</sup> Blacktop Patch hardens and cures through a process of evaporation. Cooler climates will require a longer curing time.





### **Important**

Following prolonged storage Pakmix<sup>®</sup> Blacktop Patch may feel hard in the bag. This is normal and will not adversely affect the mix. Kneading the material before opening the bag will loosen the material to a workable consistency. In cool and cold weather keep the bags of material in a warm area for at least 24 hours before using.

## **Clean Up**

Clean up with mineral spirits.

Material Safety Data Sheet available upon request.

#### 50 lb. Bag



**CAUTION • AVOID CONTACT WITH SKIN • INJURIOUS TO EYES** Pakmix® Blacktop Patch contains petroleum asphalt. As with any petroleum based material, direct contact may irritate the eyes and skin. Wear protective clothing, gloves, and eye protection when using the product. If any material gets into the eyes, rinse immediately and contact a physician. Wash exposed skin areas promptly with water. Do not take internally.

**EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES** Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.

#### KEEP OUT OF REACH OF CHILDREN

**DISCLAIMER AND LIMITATION OF LIABILITY** This material is warranted to be of good quality. Upon receipt of a claim within one year from the date of sale, defective material will be replaced or the purchase price refunded at the option of the manufacturer. Except for the foregoing, all warranties, express or implied, including merchantability and fitness for a particular purpose, are excluded. No liability is assumed for any consequential, incidental or special damages arising directly or indirectly from the use of the material.

