

Concrete Glue

Description

Pakmix[®] Concrete Glue is a liquid bonding adhesive for improving the bond between new Portland cement mixes and existing surfaces. It is easily applied by brush, roller, or sprayer.

Suggested Uses

- Bond new concrete to old concrete and masonry
- Improve holding power of new stucco or mortar to any interior or exterior clean, sound surface
- Bond mortar bed for ceramic tile to old floors and walls

Preparation

All surfaces must be structurally sound and free of oil, gas, grease, etc. before applying Pakmix[®] Concrete Glue. All glossy painted surfaces should be dulled. Paint should be at least 60 days old, not water based, and firmly applied to substrate. Stir Pakmix[®] Concrete Glue before applying. Do not shake. Apply a small test patch if the surface is questionable. Allow it to dry completely and then check to make sure there is no peeling or curling.

Items You May Need

- Roller
- Paint Brush

Packaging and Yields

1 gal. covers approximately 200-300 sq. ft. depending on the porosity and texture of the surface. Packaged in 1 qt. and 1 gal. plastic containers.

For Best Results

Use only when the temperature is 50° F and above. Surface to be covered should be damp, not soaking wet. Pakmix[®] Concrete Glue is ready to use. Do not thin. When applying concrete toppings, apply at least 1/2" thick. Toppings containing water may be applied when bond is tacky or dry. Other materials should be applied only when the bonding is still tacky (20 – 60 minutes). When bonding finish plaster, be sure the base coat is dry.

Clean Up

Clean up is easy with soap and water. Rinse tools before material hardens.

Keep From Freezing

Material Safety Data Sheet available upon request.

1 quart Bottle



1 gallon Jug



CAUTION • AVOID CONTACT WITH SKIN • INJURIOUS TO EYES Contains Ethylene Glycol and PVA emulsion. Avoid contact with skin and breathing vapors. Wear protective clothing, gloves, and eye protection when using the product. Wash exposed skin areas promptly with water. Do not take internally. Contact a physician if swallowed.

EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.

KEEP OUT OF REACH OF CHILDREN

DISCLAIMER AND LIMITATION OF LIABILITY This material is warranted to be of good quality. Upon receipt of a claim within one year from the date of sale, defective material will be replaced or the purchase price refunded at the option of the manufacturer. Except for the foregoing, all warranties, express or implied, including merchantability and fitness for a particular purpose, are excluded. No liability is assumed for any consequential, incidental or special damages arising directly or indirectly from the use of the material.