

## Fast Set Accelerator

### Description

Pakmix<sup>®</sup> Fast Set Accelerator is a premium cementitious, non-chloride accelerator designed to assist Pakmix<sup>®</sup> Concrete Mix and other Pakmix<sup>®</sup> cement based products achieve faster setting times. This product is acceptable for use with rebar, wire mesh, or metal. When mixed with Pakmix<sup>®</sup> cement products containing aggregates (concrete), rapid strength gains can be expected in addition to early setting times.

### Suggested Uses

- Fence posts
- Mailboxes
- Lamp posts
- Swing sets
- Game poles

### Directions for Use and Yields

Thoroughly mix entire contents of the container with a bag of concrete to achieve accelerated set times. Under normal conditions Pakmix<sup>®</sup> Fast Set Accelerator will achieve the following initial set times.

60 lb. bag	30-40 minutes*
80 lb. bag	45-55 minutes*
90 lb. bag	50-60 minutes*

\*Set times may vary due to temperature and cement content in the concrete mix.

Pakmix<sup>®</sup> Fast Set Accelerator may also be used to accelerate the set times of other Pakmix<sup>®</sup> cement products such as Pakmix<sup>®</sup> Sand Mix or Pakmix<sup>®</sup> Mortar Mix, etc.

### Items You May Need

- Wheelbarrow or mixing tub
- Shovel
- Mixing hoe
- Hose

### Packaging

Packaged in 1-1/2 lb. containers

## For Best Results

When using in temperatures below 45° F it is recommended to use warm water. Mix the entire contents of the container to achieve minimum set times. It is recommended to use this product only when freezing is not imminent.

## Clean Up

Clean up is easy with soap and water. Rinse tools before the material hardens.

Material Safety Data Sheet available upon request.

### 1.5 lb. Pail



**CAUTION • AVOID CONTACT WITH SKIN • INJURIOUS TO EYES** Contains Portland Cement (CAS #65997-15-1). Freshly mixed cement, mortar, concrete, grout, or stucco may cause skin injury including severe alkali burns. If exposed, wash skin promptly and repeatedly for 15 minutes and get prompt medical attention. The use of gloves and protective eye wear is recommended. If any cement or cement mixtures get into the eye, rinse immediately and repeatedly with water for 15 minutes and get prompt medical attention.

**WARNING INHALATION HAZARD** Avoid inhalation of dust from this product, which contains crystalline silica and other chemicals, which may cause lung disease and cancer. Use with mechanical ventilation or respiratory protection (dust mask).

**EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES** Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.

**KEEP OUT OF REACH OF CHILDREN**

**DISCLAIMER AND LIMITATION OF LIABILITY** This material is warranted to be of good quality. Upon receipt of a claim within one year from the date of sale, defective material will be replaced or the purchase price refunded at the option of the manufacturer. Except for the foregoing, all warranties, express or implied, including merchantability and fitness for a particular purpose, are excluded. No liability is assumed for any consequential, incidental or special damages arising directly or indirectly from the use of the material.