

Masonry Coating

Description

Pakmix[®] Masonry Coating is a Portland cement based paint for beautifying, protecting, and sealing block, brick, and concrete walls. This Masonry Coating contains Moisture Block[®] which chemically bonds to the wall surface, prohibiting the penetration of moisture.

Suggested Uses

- Sealing concrete and masonry walls
- Protecting against moisture penetration on masonry surfaces such as cellar walls
- Brightening basement walls

Preparation

All surfaces should be clean and free of oil, gas, paint, grease, etc. before applying the mix. Use Pakmix[®] Concrete Cleaner to remove stains. Repair all cracks and holes with Pakmix[®] Stop Leak or Pakmix[®] Vinyl Concrete before applying the coating. Flush the surface thoroughly with water and keep damp while applying Pakmix[®] Masonry Coating.

Directions for Mixing

Mix in a clean container. Do not mix more than can be used within 30 minutes. Add enough water to the material while mixing to obtain a thick pancake batter consistency. Never add too much water as this will weaken the product. A brush or trowel should be able to stand vertically in the material. Allow to stand for 15 minutes and then remix prior to application.

Items You May Need

- Masonry brush
- Mortar pan or pail
- Mixer shaft attachment for electric drill
- Rubber gloves
- Safety glasses

Packaging and Yields

1 – 20 lb. pail will cover up to 200 sq. ft. on a fairly smooth surface and 125 sq. ft. on a new rough block surface. One coat is sufficient in most cases. On basement walls where seepage is a problem, two coats are recommended. 1 – 50 lb. pail or bag will cover up to 500 sq. ft. on a fairly smooth surface and 300 sq. ft. on a new rough block surface. Packaged in 20 lb. pails

For Best Results

Replace part of the mixing water with Pakmix[®] Cement Fortifier. Usually 1 qt. per 50 lbs. is sufficient, but for extremely dense surfaces such as precast concrete or stone, add 2 qt. per 20 lbs. Use only when temperature is 40° F and above. Do not apply to frozen surfaces.

Clean Up

Clean up is simple and easy with soap and water. Clean the tools before the material hardens.

Material Safety Data Sheet available upon request.

20 lb. pail



CAUTION • AVOID CONTACT WITH SKIN • INJURIOUS TO EYES Contains Portland Cement (CAS #65997-15-1). Freshly mixed cement, mortar, concrete, grout, or stucco may cause skin injury including severe alkali burns. If exposed, wash skin promptly and repeatedly for 15 minutes and get prompt medical attention. The use of gloves and protective eye wear is recommended. If any cement or cement mixtures get into the eye, rinse immediately and repeatedly with water for 15 minutes and get prompt medical attention.

WARNING INHALATION HAZARD Avoid inhalation of dust from this product, which contains crystalline silica and other chemicals, which may cause lung disease and cancer. Use with mechanical ventilation or respiratory protection (dust mask).

EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.

KEEP OUT OF REACH OF CHILDREN

DISCLAIMER AND LIMITATION OF LIABILITY This material is warranted to be of good quality. Upon receipt of a claim within one year from the date of sale, defective material will be replaced or the purchase price refunded at the option of the manufacturer. Except for the foregoing, all warranties, express or implied, including merchantability and fitness for a particular purpose, are excluded. No liability is assumed for any consequential, incidental or special damages arising directly or indirectly from the use of the material.