

Paver Locking Sand (for paving stone joints)

Product

Pakmix® Paver Locking Sand is designed to eliminate or greatly reduce the need for costly maintenance of paving stone projects with the use of Quality Polymers and Specially Graded Sands and allows the following advantages.

- Greatly Slows Wash Out of Sand
- Inhibits Weed Growth
- Deters Ants and Other Insects
- Stabilizes Pavers Against Movements
- Easy to Apply

Packaging

Sealed plastic bag, can be stored outside without damaging packaging.

Yield

Per 50 lb (22.7 kg) bag: Narrow Joints 50 - 75 sq ft

Wide Joints 20 - 35 sq ft

Directions

Application of Sand:

- 1. Apply to a DRY surface with no threat of rain for 48 hours and when temperature is 50° F (10° C) and will not fall below 50° F (10° C). Do not apply in humid conditions.
- 2. Apply enough sand to fill all joints and sweep into joints.
- 3. Sweep off excess sand to avoid stains during compaction.
- 4. Compact the entire surface twice.
- 5. Repeat above steps to fill settled joints.

Application of Water:

- 1. Sweep entire surface clean to avoid staining. Use a mechanical blower to thoroughly clean paver surfaces.
- 2. Mist the joints to dampen Paver Locking Sand. Avoid direct spray to prevent washing out Polymers and Sand. Let set for 5-10 minutes.
- 3. Repeat misting in the same manner once or twice to ensure proper saturation of sand. Allow 10-15 minutes in between misting. IMMEDIATELY SWEEP OFF ANY STANDING WATER.







Directions continued

Drying Time:

Let dry **6-8 hours before light traffic** and **48 hours before heavy traffic**. This will vary depending upon temperature, humidity, wind and thickness of joints. Sand should be thumbprint hard before allowing light traffic on surface.

Precautions:

- To avoid stains and to allow for proper compaction Do not apply to wet paving stones.
- Clean entire surface area before compaction as well as misting to avoid stains.
- Avoid rain for 48 hours, humid conditions, or applying when the temperature is at or will fall below 50° F (10° C).
- Use a dust mask or suitable respiratory equipment.
- Avoid over watering until Paver Locking Sand fully sets.
- Store in a dry area.

CAUTION • AVOID CONTACT WITH SKIN • INJURIOUS TO EYES Contains Portland Cement (CAS #65997-15-1). Freshly mixed cement, mortar, concrete, grout, or stucco may cause skin injury including severe alkali burns. If exposed, wash skin promptly and repeatedly for 15 minutes and get prompt medical attention. The use of gloves and protective eye wear is recommended. If any cement or cement mixtures get into the eye, rinse immediately and repeatedly with water for 15 minutes and get prompt medical attention.

WARNING INHALATION HAZARD Avoid inhalation of dust from this product, which contains crystalline silica and other chemicals, which may cause lung disease and cancer. Use with mechanical ventilation or respiratory protection (dust mask).

EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.

KEEP OUT OF REACH OF CHILDREN

DISCLAIMER AND LIMITATION OF LIABILITY This material is warranted to be of good quality. Upon receipt of a claim within one year from the date of sale, defective material will be replaced or the purchase price refunded at the option of the manufacturer. Except for the foregoing, all warranties, express or implied, including merchantability and fitness for a particular purpose, are excluded. No liability is assumed for any consequential, incidental or special damages arising directly or indirectly from the use of the material.

