

Type S Masonry Mortar

Description

Pakmix[®] Type S Masonry Mortar Mix is a contractor grade mortar mix designed to lay brick, set block, patching, tuck point and stone work. This product is blended to achieve cube strengths of 1800 PSI @ 28 days as required by ASTM C-270 when used as directed.

Mixing Instructions

Use 17-19% water by weight (approximately 1.2 gallons per bag).

1. Pour clean water into the mixer.
2. While the mixer is on, begin adding bags of Pakmix[®] Type S Masonry Mortar Mix.
3. If the mixture becomes too thick, add additional clean water until a smooth plastic-like consistency is obtained. Excessive water reduces strength.

Installation

1. Apply approximately 1/2" to 3/4" thick mortar to a full bed base.
2. Push block or brick downward into the mortar bed and sideways against the previously laid block and tap into place.
3. Tool the joint when the mortar is resistant to thumbprints.

Curing

For hot, dry or windy conditions, the use of Pakmix[®] Cure & Seal is recommended. This aids in preventing premature drying of the mortar.

Packaging and Yields

80 lb bag will lay approximately 26 - 8" x 16" concrete blocks or 64 common bricks with 3/8" joints. Approximately 2/3 cu ft wet volume.

For Best Results

Use only when the temperature is 40° F and above. In cold weather use warm, not hot, water for mixing.

Dampen the block or the repair area before applying the new mortar to prevent premature drying of the new material.

Keep the new mortar damp for at least 3 days by an occasional fine spraying with water.

Clean Up

Clean up is easy with soap and water. Rinse the tools before material hardens.



CAUTION • AVOID CONTACT WITH SKIN • INJURIOUS TO EYES Contains Portland Cement (CAS #65997-15-1). Freshly mixed cement, mortar, concrete, grout, or stucco may cause skin injury including severe alkali burns. If exposed, wash skin promptly and repeatedly for 15 minutes and get prompt medical attention. The use of gloves and protective eye wear is recommended. If any cement or cement mixtures get into the eye, rinse immediately and repeatedly with water for 15 minutes and get prompt medical attention.

WARNING INHALATION HAZARD Avoid inhalation of dust from this product, which contains crystalline silica and other chemicals, which may cause lung disease and cancer. Use with mechanical ventilation or respiratory protection (dust mask).

EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.

KEEP OUT OF REACH OF CHILDREN

DISCLAIMER AND LIMITATION OF LIABILITY This material is warranted to be of good quality. Upon receipt of a claim within one year from the date of sale, defective material will be replaced or the purchase price refunded at the option of the manufacturer. Except for the foregoing, all warranties, express or implied, including merchantability and fitness for a particular purpose, are excluded. No liability is assumed for any consequential, incidental or special damages arising directly or indirectly from the use of the material.