

## Cement Fortifier

### Description

Pakmix<sup>®</sup> Cement Fortifier is a liquid acrylic polymer for dramatically improving the flexural, compressive, and impact strength of concrete. Pakmix<sup>®</sup> Cement Fortifier increases adhesion of new cements, grouts, and mortars to older masonry surfaces and reduces the possibility of cracking and spalling due to premature drying.

### Suggested Uses

- Add integrally to cement mixes or cement coatings
- Excellent for mixing sand topping mix to resurface concrete
- Use as an admixture with thin set

### Preparation

All surfaces must be structurally sound and free of any oil, gas, grease, paint, etc. before applying the fresh cement mix. Simply add Pakmix<sup>®</sup> Cement Fortifier at the rate of 1 part fortifier to 3 parts clean water. For more strength, add more fortifier in place of water.

### Packaging and Yields

1 gallon will mix up to approximately 300 lbs. of concrete or 250 lbs. of mortar or grout. A higher concentration of Pakmix<sup>®</sup> Cement Fortifier will mix less material. Packaged in 1 qt. and 1 gal. plastic containers.

### For Best Results

Add Pakmix<sup>®</sup> Cement Fortifier to water and then add the liquid mixture to the dry cement material. Use only when the temperature is 50° F and rising.

### Clean Up

Clean up is easy with soap and water. Rinse tools before the material hardens.

### Keep From Freezing

Material Safety Data Sheet available upon request.

## 1 quart Bottle



## 1 gallon Jug



**CAUTION • AVOID CONTACT WITH SKIN • INJURIOUS TO EYES** Pakmix<sup>®</sup> Cement Fortifier contains a water based acrylic polymer. Avoid contact with skin. Wear protective clothing, gloves, and eye protection when working with cement. If any material gets into the eyes, rinse immediately and contact a physician if swallowed. Wash exposed skin areas promptly with water. Do not take internally.

**EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES** Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.

### KEEP OUT OF REACH OF CHILDREN

**DISCLAIMER AND LIMITATION OF LIABILITY** This material is warranted to be of good quality. Upon receipt of a claim within one year from the date of sale, defective material will be replaced or the purchase price refunded at the option of the manufacturer. Except for the foregoing, all warranties, express or implied, including merchantability and fitness for a particular purpose, are excluded. No liability is assumed for any consequential, incidental or special damages arising directly or indirectly from the use of the material.