

Concrete Crack Filler

Description

Pakmix[®] Concrete Crack Filler is a flexible, ready-to-use, grey colored crack filler to repair cracks up to 1/2" wide in concrete surfaces. Repairs are fast, easy, and self-leveling.

Suggested Uses

For fast and easy patching of cracks in:

- Concrete driveways and walkways
- Patios and pool decks

Preparation

All surfaces should be clean and free of oil, gas, paint, grease, etc. before applying the material. Remove all loose particles of dirt and debris from the crack.

Directions for Mixing

Mix the contents of the container by gently shaking. Snip or cut the applicator top to the desired size. Simply squeeze the bottle pushing the material into the crack. Fill the crack until the crack filler levels with the existing surface. The area can usually be opened to traffic within 30 minutes.

Items You May Need

- Scissors or knife
- Brush for cleaning

Packaging and Yields

1 qt. will fill a crack approximately 1/2" wide x 1/4" deep x 36 linear feet long. Packaged in 1 qt. and 1 gal. plastic containers.

For Best Results

Make sure crack is clear of all dirt and debris. Do not use in temperatures below 50° F or if rain is expected. Under normal conditions the patched area may be used within 30 minutes. To speed hardening and eliminate a tacky surface, dust with dry sand or Portland cement. Cooler climates will require a longer curing time.

Clean Up

Clean immediately with soap and water. Hardened material may be removed using mineral spirits.

Keep from Freezing

Material Safety Data Sheet available upon request.

11 oz. Tube



CAUTION • AVOID CONTACT WITH SKIN • INJURIOUS TO EYES Contains Portland Cement (CAS #65997-15-1). Freshly mixed cement, mortar, concrete, grout, or stucco may cause skin injury including severe alkali burns. If exposed, wash skin promptly and repeatedly for 15 minutes and get prompt medical attention. The use of gloves and protective eye wear is recommended. If any cement or cement mixtures get into the eye, rinse immediately and repeatedly with water for 15 minutes and get prompt medical attention.

WARNING INHALATION HAZARD Avoid inhalation of dust from this product, which contains crystalline silica and other chemicals, which may cause lung disease and cancer. Use with mechanical ventilation or respiratory protection (dust mask).

EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.

KEEP OUT OF REACH OF CHILDREN

DISCLAIMER AND LIMITATION OF LIABILITY This material is warranted to be of good quality. Upon receipt of a claim within one year from the date of sale, defective material will be replaced or the purchase price refunded at the option of the manufacturer. Except for the foregoing, all warranties, express or implied, including merchantability and fitness for a particular purpose, are excluded. No liability is assumed for any consequential, incidental or special damages arising directly or indirectly from the use of the material.