

## Surface Bonding Cement

### Description

Pakmix<sup>®</sup> Surface Bonding Cement is a blend of cementitious material, fiberglass fibers, and proprietary ingredients.

### Suggested Uses

- Insulation board coating
- Dry stacked block construction
- Decorative coatings
- Patching masonry and stucco

### Preparation

All surfaces should be clean and free of foreign substances that would cause poor bonding. The surface to be coated should be moistened before applying Pakmix<sup>®</sup> Surface Bonding Cement.

### Directions for Mixing

Pour the entire bag of Pakmix<sup>®</sup> Surface Bonding Cement into a clean container. Add clean water to achieve a mortar-like consistency. Mix 1 to 2 minutes. Avoid mixing in excess of 5 minutes or fibers will break down.

### Items You May Need

- Safety glasses
- Rubber gloves
- Trowel
- Shovel or hoe
- Mortar box or wheelbarrow

### Packaging and Yields

Packaged in 50 lb. bags and will cover 50 sq. ft. x 1/8" thick.

### For Best Results

Use only when the temperature is 40° F or higher. In cold weather, use warm water. Only apply on a clean, damp surface. As with all cement products, keep moist for at least 3 days by an occasional fine misting with water.

## Clean Up

Clean up is simple and easy with soap and water. Clean the tools before the material hardens.

Material Safety Data Sheet available upon request.

## 50 lb. Bag



**CAUTION • AVOID CONTACT WITH SKIN • INJURIOUS TO EYES** Contains Portland Cement (CAS #65997-15-1). Freshly mixed cement, mortar, concrete, grout, or stucco may cause skin injury including severe alkali burns. If exposed, wash skin promptly and repeatedly for 15 minutes and get prompt medical attention. The use of gloves and protective eye wear is recommended. If any cement or cement mixtures get into the eye, rinse immediately and repeatedly with water for 15 minutes and get prompt medical attention.

**WARNING INHALATION HAZARD** Avoid inhalation of dust from this product, which contains crystalline silica and other chemicals, which may cause lung disease and cancer. Use with mechanical ventilation or respiratory protection (dust mask).

**EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES** Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.

**KEEP OUT OF REACH OF CHILDREN**

**DISCLAIMER AND LIMITATION OF LIABILITY** This material is warranted to be of good quality. Upon receipt of a claim within one year from the date of sale, defective material will be replaced or the purchase price refunded at the option of the manufacturer. Except for the foregoing, all warranties, express or implied, including merchantability and fitness for a particular purpose, are excluded. No liability is assumed for any consequential, incidental or special damages arising directly or indirectly from the use of the material.