

Description

TradeCraft Stucco Concentrate is formulated with Portland Cement certified to meet the requirements of ASTM C-150. All TradeCraft Stucco is factory blended, designed for exterior grade construction (interior when applicable). Utilizing proprietary chemically engineered admixtures to reduce cracking, increase yield and workability. TradeCraft Stucco will meet the property requirements of ASTM C-926. No chloride accelerators are used in the mix and all components are compatible with reinforcing steel.

Benefits

- Reduce Shrinkage and Cracking
- Factory Technical Support
- Increased Pump Ability

Suggested Uses

- New Construction
- Restoration and Repair Concrete Block or Brick
- Patching
- For Pre-Mixed Stucco with Integral Waterproofing see TradeCraft Waterguard Stucco Tech Data Sheet

Directions for Mixing

TradeCraft Stucco requires only clean potable water free of any known contaminants. The maximum amount of water can be mixed with this product that is consistent with optimum workability. Once the appropriate amount of water is added, mixing time is 6 minutes in a mechanical batch mixer to ensure consistency and workability of the plaster stucco.

Coverage

An 80 lb bag of Concentrate Stucco when mixed with 3 cubic feet of damp, loose sand will cover 84 sq ft at a thickness of 1/2".

Actual coverage may vary from these estimates due to variability in the sand and trade practices.

Packaging & Yields

TradeCraft Stucco Concentrate is available in 80 lb bags. Bulk or Tote bags are produced in selected markets. When mixing Concentrate add approximately 3 cubic feet of damp, loose, sand. Shelf-life is 12 months when stored in a cool dry environment.

TradeCraft Stucco Concentrate is available at leading stucco and masonry supply houses throughout the country.

Specifications

| Mix Type | Compressive Strength PSI | |
|-------------------|--------------------------|--------------|
| | 7 Days | 28 Days |
| TradeCraft Stucco | 2465.0 | |
| Control Mix | 2363.5 | 2885.5 |
| | | Avg. 2675.25 |

Caution

AVOID CONTACT WITH SKIN INJURIOUS TO EYES. Contains Portland Cement (CAS #65997-15-1). Freshly mixed cement, mortar, concrete, grout, or stucco may cause skin injury including severe alkali burns. If exposed, wash skin promptly and repeatedly for 15 minutes and get prompt medical attention. The use of gloves and protective eye wear is recommended.

Warning Inhalation Hazard: Avoid Inhalation of dust from this product, which contains crystalline silica that causes lung disease and cancer. Use with mechanical ventilation or respiratory protection (dust masks).

KEEP OUT OF REACH OF CHILDREN

EXCLUSION OF INCIDENTAL AND CONSEQUENTIAL DAMAGES Neither the manufacturer nor the retailer of this product shall be liable for any incidental or consequential damages caused by the use of this product.